

制冷食品

# 冰棒机

Popsicle machine

- 经久耐用
- 安全放心
- 操作简单
- 清洁方便

制冷食品

# 冰砖机

Ice brick machine

品质 QUALITY 诚信 INTEGRITY 专注 ABSORBED



■ CY40-1



■ CY80-2



■ CY160-4



■ CY240-6



■ CY640-16



■ CY720-18



## 产品特点 > FEATURES

1. 使用全不锈钢外壳, 美观耐用;
2. 低噪音;
3. 电子控制、温度可调;
4. 铜管制冷、蒸发面大、制冷快;
5. 采用进口压缩机、冷冻快、产量高;
6. 风冷或水冷可选;
7. 不同的冰棒模具可选不同的冰棒模具可选;
8. 已通过 CE 出口认证。

1. Full stainless steel shell, beautiful and durable;
2. Low noise;
3. With electronic control and adjustable temperature;
4. Copper tubes with large evaporation area, quick frozen;
5. With the imported compressor, quick frozen and high output;
6. Air cooling and water cooling for choice;
7. Different ice lolly molds for choice;
8. The product has passed CE certification.

## 主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	外形尺寸 Dimension (W*D*H)	冷凝方式 Cooling method	净重 N.W	电压频率 Voltage frequency	功率 Power	产量 Capacity
CY40-1	615*400*945mm	风冷 Air cooling	58KG	220V 50Hz	900W	3000pcs/24H
CY80-2	775*500*965mm	风冷 Air cooling	73KG	220V 50Hz	1250W	6000pcs/24H
CY160-4	1080*670*1050mm	风冷 Air cooling	140KG	220V 50Hz	1650W	12000pcs/24H
CY240-6	1928*936*688+260mm	风冷 Air cooling	220KG	220V 50Hz	3000W	16000pcs/24H
CY320-8	2646*936*688+260mm	风冷 Air cooling	280KG	380V 50Hz	5000W	23000pcs/24H
CY400-10	2896*936*688+260mm	风冷 Air cooling	350KG	380V 50Hz	6000W	28800pcs/24H
CY480-12	3146*936*688+260mm	风冷 Air cooling	380KG	380V 50Hz	6500W	34560pcs/24H
CY640-16	3620*935*700+260mm	风冷 Air cooling	450KG	380V 50Hz	8000W	46000pcs/24H
CY720-18	3146*1326*688+507mm	风冷 Air cooling	580KG	380V 50Hz	9500W	51840pcs/24H
CY960-24	3846*1326*688+507mm	风冷 Air cooling	800KG	380V 50Hz	11000W	69120pcs/24H
CY1280-32	4056*1716*688+817mm	风冷 Air cooling	1100KG	380V 50Hz	19000W	92160pcs/24H
CY1600-40	4556*1716*688+817mm	风冷 Air cooling	1300KG	380V 50Hz	26000W	115200pcs/24H
CY2560-64	6056*1716*688+420mm	水冷 Water cooling	1700KG	380V 50Hz	43000W	184320pcs/24H



■ CYBZJ-1



■ CYBZJ-1



■ CYBZJ-2



■ CYBZJ-2

## 产品特点 > FEATURES

1. 采用不锈钢外壳, 美观、耐用;
2. 采用进口压缩机, 冷冻快, 产量高;
4. 水冷风冷方式;
5. 采用知名丹佛斯膨胀阀;
6. 适合海鲜、食品加工厂、制冰工厂或需要大量的冰和其他地方;
7. 可接受定制。

1. Adopt stainless steel, good-looking appearance, durable;
2. With the imported compressor, quick frozen and high output;
4. Water / air cooling method;
5. Apply famous brand Danfoss expansion valve;
6. Suitable for seafood, food processing plants, ice-making factory or needs a lot of ice and other places;
7. Any output can be customized.

## 主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	冰块重量尺寸 Ice block size/weight	出冰时间 Making time(H)	冰块数量 (块) No. of ice block	机器尺寸 Dimension	冷凝方式 Coolin method	电压 / 频率 Voltage frequency	功率 Power	产量 Capacity
CYBZJ-1	152*72*600mm(5KG)	4	35	2593*958*1013+260mm	风冷 / 水冷 Air cooling/ Water cooling	380V 50Hz	6KW	1T/24H
	262*77*620mm (10KG)	4	18	2593*958*1013+260mm				
	280*120*760mm(20KG)	8	18	2316*1620*1153+260mm				
	320*120*780mm (25KG)	8	14	2416*1308*1173+260mm				
	435*145*760mm(40KG)	12	14	2626*1482*1153+260mm				
CYBZJ-2	440*160*850mm(50KG)	12	10	2636*1389*1243+260mm	风冷 / 水冷 Air cooling/ Water cooling	380V 50Hz	9.5KW	2T/24H
	152*72*600mm(5KG)	4	70	2918*1278*993+260mm				
	262*77*620mm(10KG)	4	35	3153*1006*1013+260mm				
	280*120*760mm(20KG)	8	35	3243*1306*1152+260mm				
	320*120*780mm(25KG)	8	28	3094*1306*1173+260mm				
CYBZJ-3	435*145*760mm(40KG)	12	25	4018*1118*1153+260mm	风冷 / 水冷 Air cooling/ Water cooling	380V 50Hz	11KW	3T/24H
	440*160*850mm(50KG)	12	20	3575*1192*1243+260mm				
	152*72*600mm(5KG)	4	100	3655*1278*993+260mm				
	262*77*620mm(10KG)	4	50	3353*1348*1013+260mm				
	280*120*760mm(20KG)	8	50	3343*1778*1153+260mm				
CYBZJ-4	320*120*780mm(25KG)	8	42	3992*1306*1173+260mm	风冷 / 水冷 Air cooling/ Water cooling	380V 50Hz	19KW	4T/24H
	435*145*760mm(40KG)	12	40	4218*1664*1153+260mm				
	440*160*850mm(50KG)	12	30	4243*1390*1243+260mm				
	152*72*600mm(5KG)	4	140	3455*1706*993+260mm				
	262*77*620mm(10KG)	4	72	3444*1576*1013+260mm				
CYBZJ-5	280*120*760mm(20KG)	8	72	4170*1620*1153+260mm	风冷 / 水冷 Air cooling/ Water cooling	380V 50Hz	36KW	5T/24H
	320*120*780mm(25KG)	8	54	3792*1620*1173+260mm				
	435*145*760mm(40KG)	12	50	4018*2028*1153+260mm				
	440*160*850mm(50KG)	12	40	4043*1785*1243+260mm				
	152*72*600mm(5KG)	4	168	4013*1706*993+260mm				

制冷食品

速冻柜  
Blast freezer



制冷食品

冰淇淋搅拌机 / 硬冰淇淋机  
Ice cream mixer/Hard ice cream machine

品质 QUALITY | 诚信 INTEGRITY | 专注 ABSORBED



产品特点 > FEATURES

- |  |  |
|--|--|
| <ol style="list-style-type: none"> <li>1. 全不锈钢外壳, 美观耐用;</li> <li>2. 制冷剂: R404a;</li> <li>3. 低噪声;</li> <li>4. 风冷;</li> <li>5. 开关有一个按钮, 使用方便;</li> <li>6. 采用进口压缩机或半封闭压缩机, 速冻快, 温度低;</li> <li>7. 多种容量选择;</li> <li>8. 更低温度 -80°C或定制;</li> <li>9. 产品已通过 CE 认证。</li> </ol> | <ol style="list-style-type: none"> <li>1. Full stainless steel shell, beautiful and durable;</li> <li>2.Refrigerant : R404a;</li> <li>3. Low noise;</li> <li>4. Air cooling;</li> <li>5. Switch with one button,easy using;</li> <li>6. With the imported compressor or semi-hermetic compressor, quicker-frozen and lower temperature;</li> <li>7. Various capacity for choice;</li> <li>8. Lower temperature can be -80°C or customized;</li> <li>9. The product has passed CE certification.</li> </ol> |
|--|--|

主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	CYLD-178L	CYSYD-178L	CYLD-300L	CYSYD-300L	CYLD-650L	CYSYD-650L	CYLD-1100L	CYSYD-1100L	CYLD-1400L
电压 Voltage	220V 50Hz	220V 50Hz	220/380V 50Hz	220/380V 50Hz	380V 50Hz	380V 50Hz	380V 50Hz	380V 50Hz	380V 50Hz
极限温度 Ultimate temperature	-45°C	-80°C	-45°C	-80°C	-45°C	-80°C	-45°C	-80°C	-45°C
制冷剂类别 Refrigeration	R404A	R404A+R23	R404A	R404A+R23	R404A	R404A+R23	R404A	R404A+R23	R-404A
冷凝方式 Cooling way	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling
额定功率 / 千瓦 Power	1.7KW	2.5KW	2.5KW	5.5KW	5.5KW	10KW	6.2KW	12KW	8KW
外形尺寸 Dimensions	880*740*1320mm	880*740*1320mm	800*1136*1614mm	800*1136*1614mm	1400*1142*1872mm	1400*1295*1872mm	1637*1210*2070mm	1637*1210*2070mm	2155*1250*2150mm
重量 N.W	130KG	220KG	280KG	380KG	420KG	520KG	490KG	680KG	665KG
托盘数量 Trays quantity	6-8层 6-8layers	6-8层 6-8layers	10-12层 10-12layers	10-12层 10-12layers	10*2层 10*2layers	10*2层 10*2layers	15*2层 15*2 layers	15*2层 15*2layers	30层 30layers
托盘尺寸 Trays size	400*600*20mm	400*600*20mm	400*600*20mm	400*600*20mm	400*600*20mm	400*600*20mm	400*600*20mm	400*600*20mm	400*600*20mm

冰淇淋搅拌机 Ice cream mixer

产品特点 > FEATURES

自动款冰淇淋搅拌机: 电脑版控制, 多种模式选择, 一键启动, 自动清洗搅拌, 省去人工手动操作。

1. 实现冰淇淋和水果、坚果、奶昔、一个完美结合, 创造出更多种类天然水果口味的冰淇淋。
2. 用手动控制, 以促进嵌套的水果碎和调速。
3. 喷气机清洗, 准备好使用, 能有效解决冰淇淋在生产过程中不同的水果和异味问题。
4. 螺旋搅拌叶片, 搅拌头的底部提供了方便的打破冰冻水果片。
5. 一个带有漏斗形受搅拌的帽子, 帽子的形状取决于可以发挥多种形状的水果冰淇淋。

Computer version control, a variety of mode selection, one-click start, automatic cleaning and mixing, eliminating manual operation

1. Achieve ice cream and fruit,nuts,milkshakes,a perfect combination to create a greater variety of natural fruit flavors of ice cream.
2. With manual control,to facilitate nesting of fruit crushing and speed adjustment.
3. Jet cleaning,ready to use,effective solution to ice cream in the production process of different fruits and odor problems.
4. Spiral mixing blades,the bottom of the mixing head with a convenient break the frozen fruit pieces.
5. Stir with a funnel shape under the cap,depending on the shape of hats can play a variety of shapes of fruit cream.



主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	CYBQL-178T	CYZD-178T
电压 Voltage	220V 50Hz	220V 50Hz
功率 Power	750W	750W
尺寸 Dimensions	320*560*650mm	320*580*830mm
净重 N.W	50KG	63KG

硬冰淇淋机 Hard ice cream machine

产品特点 > FEATURES

意大利款硬冰淇淋机

1. 采用直冷式缸体采用高精度数控加工, 制冷缸快速制冷成型均匀。
2. 弹性不锈钢搅拌轴, 与缸体贴合度更紧密, 提高膨化率, 口感更细腻。
3. 丹佛斯膨胀阀自动调节制冷流量。
4. 丹佛斯水流调节阀, 可自动根据系统高低压力精准调节水流流量, 以达到节约水源。
5. 全不锈钢面板。

硬冰淇淋机

1. 缸体采用直冷环绕式制冷缸快速制冷成型均匀。
2. 膨化阀自动调节制冷流量。
3. 采用无皮带式减速器连接带动不锈钢加硬搅拌轴更耐用, 更好的抗噪音, 无振动。
4. 亚克力透明式面板可观看成型程度硬度。

Italian hard ice cream machine

- 1.The straight-cooled cylinder adopts high-precision CNC processing, and the refrigeration cylinder is quickly cooled and formed evenly.
- 2.The elastic stainless steel mixing shaft is more closely fitted with the cylinder, improving the swelling rate and making the taste more delicate.
- 3.The Danfoss expansion valve regulates the cooling flow automatically .
- 4.Danfoss water flow control valve can adjust the water flow automatically according to the high and low pressure of the system to achieve water conservation.
- 5.All stainless steel panel.

Hard ice cream machine

- 1.The cylinder body adopts a direct cooling surround refrigeration cylinder for rapid and uniform refrigeration molding.
- 2.The expansion valve automatically adjusts the refrigeration flow rate.
- 3.Using a belt less reducer to connect and drive the stainless steel reinforced mixing shaft is more durable, better noise resistant, and vibration free.
- 4.The acrylic transparent panel can observe the degree of molding and hardness.

主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	CY-116	CY-618	CY-N28	CY-N45	CY-N60	CY-N80	CY-N90	CY-IT90
制冷剂 Refrigerant	R22	R22/R410	R22/R410	R22/R410	R22/R410	R404A	R404A	R404
料缸容量 Cylinder capacity	4.3L*1	4.3L*1	10L*1	15L*1	15L*1	30L*1	50L*1	18L*1
产量 Capacity	16L-20L/H	16L-20L/H	28L-32L/H	45L/H	50-60L/H	100-110L/H	120-150L/H	80-90L/H
冷凝方式 Cooling method	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	风冷 Air cooling	水冷 Water cooling
尺寸 Dimensions	525*490*640mm	530*500*700mm	605*765*1370mm	605*765*1370mm	605*765*1370mm	605*1000*1370mm	680*1330*1380mm	850*520*1315mm
电压 Voltage	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz	220/380V 50Hz	380V 50Hz	380V 50Hz
额定功率 Rated power	1400W	1400W	2300W	2800W	3500W	7200W	8800W	5500W
净重 N.W	60KG	60KG	100KG	120KG	140KG	160KG	400KG	298KG



制冷食品

软冰淇淋机 / 牛奶雪花冰机  
Soft ice cream machine/Milk snowflake ice machine



制冷食品

老化机 / 膨化搅拌机  
Aging machine/Bulking mixer

品质 QUALITY | 诚信 INTEGRITY | 专注 ABSORBED

软冰淇淋机 Soft ice cream machine



CY-628T CY-828T CY-828 CY-6228 CY-8238H CY-8668

产品特点 > FEATURES

1. 全不锈钢外壳;
  2. 制冷剂可选择;
  3. 低噪音;
  4. 自带膨化功能;
  5. 数码显示系统;
  6. 机器故障自动识别报警功能;
  7. 已通过 CE 出口认证。
1. Many color for choice;  
2. Refrigerant: R404a/R22/R410a R404a/R22/R410a;  
3. Low noise;  
4. Bulking function;  
5. Digital display system;  
6. Failure warning;  
7. The product has passed CE certification.

主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	CY-628T	CY-828T	CY-828	CY-6228	CY-8238H	CY-8668
制冷剂 Refrigerant	R22/R404/R410	R22/R410/R404	R22/R410/R404	R22/R404/R410	R22/R404/R410	R22/R404/R410
料缸容量 Cylinder capacity	6L*2	6L*2	6L*2	6L*2	6L*2	6L*2
产量 Capacity	26L-30L/H	20L-28L/H	20L-28L/H	26L-30L/H	28L-32L/H	50-60L/H
尺寸 Dimension	540*710*780mm	540*710*815mm	540*590*1360mm	540*590*1360mm	540*590*1360mm	580*700*1500mm
电压 Voltage	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz	220/380V 50Hz
功率 Power	2200W	2200W	2200W	2400W	2400W	3500W
净重 N.W	90KG	85KG	99KG	99KG	99KG	180KG

牛奶雪花冰机 Milk snowflake ice machine

产品特点 > FEATURES

1. 一键式启动操作简单, 设备启动快, 滚筒转速快, 出冰量大;
  2. 滚筒下面水盒可拆卸, 便于清洁;
  3. 风冷机型, 不受水源限制, 插电即可用;
  4. 带智能定量功能, 小中大杯设定, 精准控量;
  5. 调速旋钮 0-100, 根据原料任意调节, 雪花产量、粗细随之调节。
1. One-button start operation is simple, equipment start fast, drum speed is fast, and ice output is large;  
2. The water box under the drum is removable, which is easy to clean;  
3. Air-cooled model, not limited by water source, plugged in and used;  
4. With intelligent quantitative function, small/medium/large cup setting, precise control;  
5. Speed control knob 0-100, adjust it arbitrarily according to the raw materials, and adjust the snowflake quantity and thickness accordingly.



CY-XB200 CY-XB250



主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	CY-XB200	CY-XB250
日产量 Capacity	160-200KG/24H	180-220KG/24H
外型尺寸 Machine	375*583*550mm	370*580*680mm
功率 Power	1100W	1400W
电压 Voltage	220V 50Hz	220V 50Hz
重量 N.W	45KG	55KG
制冷剂 Refrigerant	R290	R404a

老化机 Aging machine



CYLH-150L CYLH-300L

产品特点 > FEATURES

冰淇淋老化均质后料液要及时冷却, 温度一般为 6°C。冷却的目的: (1) 可以挥发掉一部分不良气体; (2) 防止脂肪上浮与酸度增高; (3) 为老化工作做好准备。老化又名物理成熟, 主要使料液的物理性质有所改变。通过老化, 可以进一步提高料液的粘度和稳定性, 防止料液中游离水析出或脂肪上浮, 并可缩短凝冻时间。正常情况下, 冷却温度为 6°C, 时间为 12 小时。但料液中总干物质含量越高, 老化温度就低, 老化时间也可缩短。

After the ice cream aging homogenization, the liquid should be cooled in time, and the temperature is generally 6°C. The purpose of cooling: (1) can volatilize part of the bad gas; (2) Prevent fat from floating and increase acidity; (3) Prepare for aging work. Aging, also known as physical maturity, mainly changes the physical properties of the feed liquid. Through aging, the viscosity and stability of the feed liquid can be further improved, the free water in the feed liquid can be prevented from precipitation or fat floating, and the freezing time can be shortened. Under normal conditions, the cooling temperature is 6°C and the time is 12 hours. However, the higher the total dry matter content in the feed liquid, the lower the aging temperature, and the aging time can be shortened.

主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	CYLH-150L	CYLH-300L
电压 Voltage	220V 50Hz	220/380V 50Hz
制冷剂 Refrigerant	R22/R410	R22/R410
冷藏温度 Cooling temp.	2-10°C	2-10°C
额定功率 Power	2KW	3KW
尺寸 Dimension	800*750*1310+300mm	1160*1020*1330+300mm
净重 N.W	129.5KG	200KG

膨化搅拌机 Bulking mixer

产品特点 > FEATURES

1. 根据冰淇淋粉比例跟水 (热水) 搅拌均匀后, 倒入原料桶内通上电膨化机的电机开始高速旋转;
  2. 高速旋转下高温高压下, 物质中的水分在极短的时间里瞬间汽化并膨胀, 使物质体积急剧膨胀的过程;
  3. 冰淇淋原料含有蛋白质和糖等, 都含有水分, 经过膨化机的膨化处理后, 可以使冰淇淋的口感更加绵密和细腻。
1. According to the proportion of ice cream powder and water (hot water), stir evenly, pour into the raw material bucket and start to rotate at high speed;  
2. Under high temperature and high pressure under high-speed rotation, the water in the substance instantaneously vaporizes and expands in a very short time, making the material volume expand rapidly;  
3. Ice cream raw materials contain protein and sugar, etc., which contain water. After the puffing treatment of the puffing machine, the taste of ice cream can be made more dense and delicate.



CYPH-40L CYPH-60L

主要技术参数 > MAIN TECHNICAL PARAMETERS

型号 Model	CYPH-40L	CYPH-60L	CYPH-120L
电压 Voltage	220V 50Hz	220V 50Hz	220V 50Hz
功率 Power	370W	370W	370W
尺寸 Dimensions	640*600*850+260mm	640*600*850+260mm	800*800*850+260mm
净重 N.W	30KG	35KG	45KG